

Declaration of performance No. LE-12058/10

1. **Identification code of product** DIDO-12058
2. **Code for identification of product in accordance with CPR Construction Products Regulation article 11 para. 4**
Dietfurter Dolomite DIDO-12058
Dolomite Limestone
Brown / Grey / Beige
Treuchtlingen-Dietfurt, Kaldorf, Germany
3. **Intended use of product as per harmonized technical specification**
Tiles of natural stone for floor and stairs for interior and exterior application EN 12058
4. **Trade name and address of manufacturer**
Trade name Dietfurter Dolomite
Address: FRANKEN-SCHOTTER GmbH & Co. KG
Hungerbachtal 1
D-91757 Treuchtlingen-Dietfurt
5. **Name and address of authorized and commissioned person as per BauPVO article 12 para. 2**
not relevant
6. **System to evaluate and test the reliability of performance of the product**
System 4
7. **The notified institution of product control certification**
TÜV Rheinland LGA Products GmbH identification no. 0780, performed the essential characteristics by product control and issued the certificate.
8. **Name and code number of the technical office in case of a declaration of performance concerning a product evaluated by a european technical office**
not relevant
9. **Essential characteristics**

Essential characteristics	Performance	Harmonised techn. specification
reaction to fire	class A1	Without test (see 96/603/EG)
flexural strength	LEV = 6,5 MPa MV = 9,8 MPa S = 1,7	EN 12058: 2015
density	2590 kg/m ³	
abrasion [cm ³ /50cm ²]	UEV = 19,8	
slip resistance [SRV]	wet / dry [MV]: 35 / 45	
honed C`220 / 7	NPD / NPD	
polished	30 / 50	
castellina	NPD / NPD	
honed + brushed	NPD / NPD	
sandblasted + brushed	NPD / NPD	



Identification code of the notified testing center
0780

Name and address of the producer
FRANKEN-SCHOTTER GmbH & Co. KG
Hungerbachtal 1
D-91757 Treuchtlingen-Dietfurt

Last two digits of the year in which the evaluation was first issued
13

Reference no. of the declaration of performance
LE-12058/10

No. of the harmonized technical specification
EN 12058

Intended use of the building product
Tiles of natural stone for floor and stairs for interior and exterior application

Identification code of the product results
DIDO-12058

Classification of the declared performance:

reaction to fire class A1

flexural strength LEV = 6,5 MPa
MV = 9,8 MPa
S = 1,7

density 2590 kg/m³

abrasion [cm³/50cm²] UEV = 19,8

slip resistance [SRV] wet / dry [MV]:
honed C`220 / 7 35 / 45
polished NPD / NPD
castellina 30 / 50
honed + brushed NPD / NPD
sandblasted + brushed NPD / NPD

10. **The performance of the product according to no. 1 and no. 2 corresponds to the declared performance in accordance with no. 9. Responsible for the declaration of performance is solely the producer according to no. 4 Signed for on behalf of the producer and in the name of the producer**

91757 Treuchtlingen-Dietfurt, 29.01.2019

place and date of issue

signed