

Declaration of performance No. LE-1469/9

1. **Identification code of product** JGEL-1469
2. **Code for identification of product in accordance with CPR Construction Products Regulation article 11 para. 4**
 Jura Limestone beige JGEL-1469
 Limestone
 Beige
 Treuchtlingen-Dietfurt, Kaldorf, Germany
3. **Intended use of product as per harmonized technical specification**
 Tiles of natural stone for wall cladding for exterior and interior application EN 1469
4. **Trade name and address of manufacturer**
 Trade name Jura Limestone beige
 Address: FRANKEN-SCHOTTER GmbH & Co. KG
 Hungerbachtal 1
 D-91757 Treuchtlingen-Dietfurt
5. **Name and address of authorized and commissioned person as per BauPVO article 12 para. 2**
 not relevant
6. **System to evaluate and test the reliability of performance of the product**
 System 3
7. **The notified institution of product control certification TÜV Rheinland LGA Products GmbH identification no. 0780, performed the essential characteristics by product control and issued the certificate.**
8. **Name and code number of the technical office in case of a declaration of performance concerning a product evaluated by a european technical office**
 not relevant
9. **Essential characteristics**

Essential characteristics	Performance	Harmonised techn. specification
reaction to fire	class A1	Without test (see 96/603/EG)
flexural strength	LEV = 10,2 MPa MV = 13,5 MPa S = 1,6	EN 1469: 2015
breaking load at anchor hole (d1 =10 mm)	LEV = 1200 N MV = 1750 N S = 260	
durability flexural strength before F-T-C	MV = 13,5 MPa	
flexural strength after 56 F-T-C	MV = 12,5 MPa	
density	2570 kg/m ³	

10. **The performance of the product according to no. 1 and no. 2 corresponds to the declared performance in accordance with no. 9. Responsible for the declaration of performance is solely the producer according to no. 4 Signed for on behalf of the producer and in the name of the producer**

91757 Treuchtlingen-Dietfurt, 01.07.2016

place and date of issue



signed



Identification code of the notified testing center
0780

Name and address of the producer
FRANKEN-SCHOTTER GmbH & Co. KG
Hungerbachtal 1
D-91757 Treuchtlingen-Dietfurt

Last two digits of the year in which the evaluation was first issued
13

Reference no. of the declaration of performance
LE-1469/9

No. of the harmonized technical specification
EN 1469:

Intended use of the building product
Tiles of natural stone for wall cladding for exterior and interior application

Identification code of the product results
JGEL-1469

Classification of the declared performance:

reaction to fire class A1

flexural strength
LEV = 10,2 MPa
MV = 13,5 MPa
S = 1,6

breaking load at anchor hole
(d1 =10 mm)
LEV = 1200 N
MV = 1750 N
S = 260

durability
flexural strength before F-T-C
MV = 13,5 MPa

flexural strength after 56 F-T-C
MV = 12,5 MPa

density
2570 kg/m³