

# Declaration of performance No. LE-1469/15

1. **Identification code of product** WADO-1469
2. **Code for identification of product in accordance with CPR Construction Products Regulation article 11 para. 4**  
Wachenzeller Dolomite WADO-1469  
Dolomite Limestone  
Brown / Grey / Beige  
Wachenzell, Germany
3. **Intended use of product as per harmonized technical specification**  
Tiles of natural stone for wall cladding for exterior and interior application EN 1469
4. **Trade name and address of manufacturer**  
Trade name Wachenzeller Dolomite  
Address: FRANKEN-SCHOTTER GmbH & Co. KG  
Hungerbachtal 1  
D-91757 Treuchtlingen-Dietfurt
5. **Name and address of authorized and commissioned person as per BauPVO article 12 para. 2**  
not relevant
6. **System to evaluate and test the reliability of performance of the product**  
System 3
7. **The notified institution of product control certification TÜV Rheinland LGA Products GmbH identification no. 0780, performed the essential characteristics by product control and issued the certificate.**
8. **Name and code number of the technical office in case of a declaration of performance concerning a product evaluated by a european technical office**  
not relevant
9. **Essential characteristics**

Essential characteristics	Performance	Harmonised techn. specification
reaction to fire	class A1	Without test (see 96/603/EG)
flexural strength	LEV = 6,5 MPa MV = 9,0 MPa S = 1,3	EN 1469:  2015
breaking load at anchor hole ( d1 =15 mm )	LEV = 1300 N MV = 2000 N S = 390	
durability flexural strength before F-T-C	MV = 9,0 MPa	
flexural strength after 56 F-T-C	MV = 7,5 MPa	
density	2650 kg/m <sup>3</sup>	

10. **The performance of the product according to no. 1 and no. 2 corresponds to the declared performance in accordance with no. 9. Responsible for the declaration of performance is solely the producer according to no. 4 Signed for on behalf of the producer and in the name of the producer**

91757 Treuchtlingen-Dietfurt, 10.12.2018

place and date of issue

*Karl Trab*

signed



**Identification code of the notified testing center**  
0780

**Name and address of the producer**  
FRANKEN-SCHOTTER GmbH & Co. KG  
Hungerbachtal 1  
D-91757 Treuchtlingen-Dietfurt

**Last two digits of the year in which the evaluation was first issued**  
18

**Reference no. of the declaration of performance**  
LE-1469/15

**No. of the harmonized technical specification**  
EN 1469:

**Intended use of the building product**  
Tiles of natural stone for wall cladding for exterior and interior application

**Identification code of the product results**  
WADO-1469

**Classification of the declared performance:**

**reaction to fire** class A1

**flexural strength**

LEV = 6,5 MPa  
MV = 9,0 MPa  
S = 1,3

**breaking load at anchor hole**

( d1 =15 mm )  
LEV = 1300 N  
MV = 2000 N  
S = 390

**durability**

flexural strength before F-T-C  
MV = 9,0 MPa

flexural strength after 56 F-T-C  
MV = 7,5 MPa

**density**

2650 kg/m<sup>3</sup>